

# StoneHenge™ II

StoneHenge™  
II



## Specifications: StoneHenge™ II

## Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4 ohm
Sensitivity dB @ 2.83V/1M	90dB
Sensitivity dB @ 1W/1M (2)	87dB
Frequency Response ( $\pm 3$ dB)	80 Hz - 19 kHz
Frequency Response ( $\pm 10$ dB)	70 Hz - 19 kHz
Max. Program Power	300W
Max. Continuous Power RMS	150W
Power Output	150 Watts
Max. Power SPL @ 1 M	109.0 dB
Transformer Options	25/70.7/100 V
Transducer - Low Frequency Driver	8" Polypropylene Cone w/ Butyl Rubber Surround
Transducer - High Frequency Driver	1" Weather Resistant
Colors	Sandstone, Grey, and Brown
Tweeter - part	1" Weather Resistant
Height (SM = Height)	450.9 mm / 17.75"
Diameter (SM = Width)	438.2 mm / 17.25"
Weight	20.4 kg / 45 lb
Shipping Weight	22.7 kg / 50 lb
Accessories Optional	120 watt XFMR, Security Bracket (RSB1)
Regulatory - CE	approved
Applications	The StoneHenge II is perfect for large outdoor living spaces, themed entertainment, hotels and resorts, outdoor restaurants and other large venues.

---

# StoneHenge™ II

StoneHenge™  
II



---

## Description

Superb musicality and high power handling combined with clear, understandable speech make the StoneHenge II ideal for both residential and commercial settings. This two-way speaker incorporates a granite exterior with an 8" coax woofer and 1" tweeter. An optional 120W transformer is available for installation of the StoneHenge II in 70V systems.

## Applications

The StoneHenge II is perfect for large outdoor living spaces, themed entertainment, hotels and resorts, outdoor restaurants and other large venues.

## Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which

explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

## Technical Data and Specification Tools

### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com).

Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

### Data Acquisition and

## Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

## Architectural Specifications

No specifications currently.

### Rockustics

8005 W 110th Street, Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<https://rockustics.mseaudio.com>  
All SoundTube products come with a 5-year limited warranty.

---

# StoneHenge™ II

StoneHenge™  
II



---

## Optional Accessories

120 watt XFMR



**Security Bracket (RSB1)**