

SurroundStone™ 8

SURROUNDSTONE™
8



Specifications: SurroundStone™ 8

Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4.0 ohm
Sensitivity dB @ 2.83V/1M	91.0dB
Sensitivity dB @ 1W/1M (2)	88.0dB
Frequency Response (± 3 dB)	61 Hz - 22 kHz
Frequency Response (±10 dB)	38 Hz - 22 kHz
Max. Program Power	140 Watts
Max. Continuous Power RMS	70 Watts
Max. Power SPL @ 1 M	106.5dB
Tap Selector	Wire leads
Transformer Options	25V \ 70.7V \ 100V
Transducer - Low Frequency Driver	8" Weather Resistant
Transducer - High Frequency Driver	.75" Dome
Colors	Brown, Gray or Sandstone
Tweeter - part	.75" Dome
Driver - part	8" Coax
Inputs	Wire lead
Height (SM = Height)	355.6 mm / 14.0"
Diameter (SM = Width)	438.2 mm / 17.25"
Weight	20.4 lb / 45 lb
Shipping Weight	23.9 kg / 52 lb
Accessories Optional	Security Bracket (RSB1),65 WATT XFMR
Regulatory - CE	approved
Applications	This 100 watt speaker is perfect for large gardens, reception centers, themed entertainment and other outdoor spaces.

SurroundStone™ 8

SURROUNDSTONE™
8



Description

The SurroundStone 8 offers inconspicuous yet encompassing sound. An 8" coax woofer and an .75" dome tweeter are incorporated in a sealed, on-ground enclosure with omnidirectional dispersion. Available in three colors.

Applications

This 100 watt speaker is perfect for large gardens, reception centers, themed entertainment and other outdoor spaces.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed

according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<https://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

SurroundStone™ 8

SURROUNDSTONE™
8



Optional Accessories



Security Bracket (RSB1)

65 WATT XFMR