

XT-SurroundStone™ 8

XT-SURROUNDSTONE™
8



Specifications: XT-SurroundStone™ 8

Mounting hardware included

Nominal Impedance	4 ohm
Impedance (min)	4.0 ohm
Sensitivity dB @ 2.83V/1M	91.0dB
Sensitivity dB @ 1W/1M (2)	88.0dB
Frequency Response (± 3 dB)	60 Hz - 22 kHz
Frequency Response (± 10 dB)	50 Hz - 22 kHz
Max. Program Power	140w
Max. Continuous Power RMS	70w
Max. Power SPL @ 1 M	106.5dB
Tap Selector	5-Position Rotary Switch w/ Transformer Bypass Position
Transformer Options	25/70.7/100 V w/ 8 Ω Bypass
Transducer - Low Frequency Driver	8" Polypropylene Cone w/ Butyl Rubber Surround
Transducer - High Frequency Driver	.75" Silk Dome
Colors	Brown, Grey, Sandstone
Tweeter - part	.75" Silk Dome
Inputs	Wire lead
Height (SM = Height)	355.6 mm / 14.0"
Diameter (SM = Width)	438.2 mm / 17.3"
Weight	23.9 kg / 52.7 lb
Shipping Weight	25.4 kg / 56.0 lb
Accessories Optional	Security Bracket (RSB1)
Regulatory - CE	approved

Applications

Use the XT-SurroundStone 8 in theme parks, large amusement parks, courtyards, shopping plazas and any other outdoor setting requiring omnidirectional music and paging.

XT-SurroundStone™

8

XT-SURROUNDSTONE™
8



Description

The XT-SurroundStone 8 is ideal for large commercial outdoor installations, with inconspicuous yet encompassing sound. An 8" coax woofer and .75" dome tweeter are incorporated in a sealed, on-ground enclosure with omnidirectional dispersion. A 64 watt transformer is provided for use in 70V systems. Available in three colors.

Applications

Use the XT-SurroundStone 8 in theme parks, large amusement parks, courtyards, shopping plazas and any other outdoor setting requiring omnidirectional music and paging.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which

explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently

collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<https://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

XT-SurroundStone™ 8

XT-SURROUNDSTONE™
8



Optional Accessories



Security Bracket (RSB1)